

HD35UST

1080p ultra short throw home entertainment projector



- Lights on viewing bright 3600 lumens
- Ultra short throw lens 100" image from less than half a metre away
- Enjoy live sports, TV shows and gaming in Full HD 1080p
- Easy to setup horizontal and vertical keystone and four corner adjustment

Experience a super-sized 100-inch image with this ultra short throw projector placed just 30cm away from a wall or screen. Perfect for live sports, TV shows, films and gaming with it's bright, razor sharp images with optimum colour performance even with the lights on.

An integrated speaker provides great sound and two HDMI inputs enables an easy setup. You can even turn it into a smart projector by connecting a HDMI dongle like the Google Chromecast[™], Amazon Fire Stick or Apple TV[™] to play games, stream videos and share photos on the big screen in the comfort of your own home.

Specifications

Display/image	
Display technology	
Resolution	1080p Full HD (1920x1080)
Brightness	3,600 lumens
Contrast ratio	30,000:1
Native aspect ratio	16:9
Aspect ratio - compatible	4:3, 16:9
Keystone correction - horizontal	4
Keystone correction - vertical	4
Horizontal scan rate	15.375 ~ 91.147Khz
/ertical scan rate	24 ~ 85(120 for 3D)Hz
Uniformity	80%
Screen size	2.03m - 2.54m (80in - 100in)(Diagonal)
Lamp info	2.00m - 2.04m (00m - 100m (Diagonal)
Lamp mo Light source	Lamp
Light source	240
Lamp watts	240 4000 (Bright), 12000 (Dynamic), 10000 (Eco), 15000 (Eco+)
	тоор (Engini), тероор (Eynamilic), торор (Eco), торор (Eco+)
Optical Throw ratio	0.25:1
Projection distance (m)	0.251 0.45m - 0.56m
Zoom type	Fixed
	Fixed 3.72
Focal length (mm)	
Native offset	118%
Connectivity Connections	Inputs 1 x HDMI 1.4a 3D support + MHL, 1 x HDMI 1.4a
	3D support, 1 x VGA (YPbPr/RGB), 1 x Composite video, 1 x Audio 3.5mm, 2 x USB-A reader/wireless Outputs 1 x VGA, 1 x Audio 3.5mm Control 1 x RS232, 1 x RJ45
General	
Noise level (typical)	26dB
PC compatibility	FHD, UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac
2D compatibility	NTSC M/J, 3.58MHz, 4.43MHz PAL B/D/G/H///M/N, 4,43MHz SECAM B/D/G/K/K1/L, 4.25/4.4MHz 480i/p, 576i/p, 720p(50/60Hz), 1080i(50/60Hz), 1080p(50/60Hz)
3D compatibility	Side-by-Side:1080i50 / 60, 720p50 / 60 Frame-pack: 1080p24, 720p50 / 60 Over-Under: 1080p24, 720p50 / 60
3D	Full 3D
Security	Security bar, Kensington Lock, Password protected interface
OSD / display languages	25 languages: Arabic, Czech, Danish, Dutch, English, Farsi, Finnish, French, German, Greek, Hungarian, Indonesian, Italian, Japanese, Norwegian, Polish, Portuguese, Romanian, Russian, Chinese (simplified), Spanish, Swedish, Chinese (traditional), Turkish, Vietnamese
Operating conditions	5°C ~ 40°C, Max. Humidity 85%, Max. Altitude 3000m
Remote control	Data remote with laser and mouse function
Speaker count	1
Watts per speaker	16W
In the box	AC power cord Remote control 2x AAA batteries Basic user manual
Networking	_ *******
LAN - control	Yes
LAN - display	Yes
Power	
Power supply	100 ~ 240V, 50 ~ 60Hz
	0.5W
Power consumption	0.5W
Power consumption (standby)	
Power consumption (standby) Power consumption (max)	0.5W 275W
Power consumption (standby) Power consumption (max) Weight and dimensions	275W
Power consumption (standby) Power consumption (max)	



Copyright © 2018, Optoma and its logo is a registered trademark of Optoma Corporation. Optoma Europe Ltd is the licensee of the registered trademark. All other product names and company names used herein are for identification purposes only and may be trademarks or registered trademarks of their respective owners. Errors and omissions excepted, all specifications are subject to change without notice. All images are for representation purposes only and may be simulated. 14092018114114