
PN-HW431T

A fast and accurate tool for teams that collaborate









- BIG PAD for smaller office meeting spaces
- "Pen-on-paper" user experience with fast and responsive IR 20 point touch
- Powerful data organisation and collaboration with SHARP Touch Viewer application
- 43" (108cm) size with 3840 x 2160 pixels
- Intuitive writing, drawing and annotation with SHARP Pen software
- Attractive touch stylus with 2mm tip



Specifications

DISPLAY MODULE DATA

Panel Technology LCD Native Resolution (Pixels) 3.840 x 2.160 Diagonal Size (inches / cm) 42.5 / 108 **Aspect Ratio** 16:9 **Backlight Technology** LED, edge lit Brightness (cd/m2) 350 **Contrast Ratio** 4.000: 1 1.07 billion **Display Colours** 0,2451 x 0,2451 Pixel Pitch (mm H/V) Viewing Angle (H/V)0 CR >10 178 / 178 Active Screen Area (H/V) mm 941.2 x 529.4

TOUCH INTERFACE SPECIFICATION

Technology Infrared
Number of Touch Points 20
Safety Glass Thickness (mm) 3.2
Coating / Filter AG
Pen Mode / Finger Mode • •
PC Connection Method USB

Operating System Compatibility Windows10(32 / 64bit)

SAFETY AND ENVIRONMENT (EUROPE)

CE, CB Report •
Mercury Content (mg) 0

INSTALLATION

Landscape .
Portrait .
Mounting (VESA/Number of Points/Pitch mm) 4/20

Mounting (VESA/Number of Points/Pitch mm) 4 / 200 x 200
Mounting (Other) Backward Tilt (0 to 20, 45 degrees)

Mounting Screw Specification (Size/Max M6

Length)

CONNECTIVITY (AUDIO/VIDEO) OUTPUT

Audio/Headphone 3.5mm Jack 1
External Speaker 10W + 10W

ACCESSORIES

Battery

 Remote Control Transmitter
 STD

 Operation Manual
 STD

 Installation Set-Up Manual
 STD

 CD Rom
 STD

Software SHARP Pen Software, Sharp Touch

 Power Cord
 STD

 USB Cable
 STD

 Pen
 STD

KEY SPECIFICATIONS

Limited Manufacturer's Warranty (yrs.)

Built in Speakers (W)

Computer Input - Plug and Play

Power Management

Cabinet Colour

Fanless

Residual Image Reduction Feature

Multi Language OSD

Remote Management

Adjustment Lock Feature

Colour Temperature Adjustment

Self-Adjust

Self-Adjust

- 10W + 10W

Black

Fack

- 20W

- 3W

- 3W

- 4W

- 4W

- 5W

- 5W

- 5W

- 6W

- 7W

POWER SUPPLY AND OPERATING ENVIRONMENT

Operating Voltage(ACV) / Frequency(Hz) 100V-240V AC, 50 / 60Hz Power Consumption (W) (Operating MAX) 115 Power Consumption (W) (Standby) 0.5 Operating Temperature (oC) 5-35 . Humidity (%) 20-80 Heat Dissipation (BTU/h) MAX 392 Power consumption standby (IEC 62301:2005) 0.5 Power consumption off mode (IEC 62301:2005)

WEIGHTS AND MEASURES

Shipping Weight (Kg)

 Bezel Size (L/R) mm
 16 / 16

 Bezel Size (U/L) mm
 16 / 16

 Product Dimensions (W/H/D) mm
 1007 x 598 x 72

 Shipping Carton Dimensions (W/H/D) mm
 tbd

 Product Weight Without Stand (Kg)
 16

tbd

CONNECTIVITY (AUDIO/VIDEO) INPUT

 HDMI
 3

 VGA
 1

 Audio 3.5mm Jack
 1

CONNECTIVITY (CONTROL/SERIAL DATA)

 RS232C IN
 1

 LAN Port
 1

 USB
 1



